



APACHE X561

SEMUA offers a range of pneumatic Airless Painting Pump able to cope with virtually all types of painting environment, whether on site where the need is for maneuverability or in a fixed environment such as paint booth.

Tried and tested throughout the world the SEMUA range of paint pumps, offers unparalleled rugged efficient operation applying paint quickly and accurately.

FEATURES

- Heavy duty air regulator
- 10 Inch size Air Motor
- Complete with all painting accessories and ready to use.

INDUSTRIES SERVED

- Construction
- Steel Fabrication
- Shipyards
- High viscosity coating
- Protective coating

TECHNICAL DATA	X-45:1	X-56:1	X-68:1
Fluid pressure ratio	45:1	56:1	68:1
Delivery (Litre/min)	15.8	13.7	11.4
CC per cycle	263	228	190
Max. pump speed/min	60	60	60
Air motor diameter (inch; mm)	10 (254)	10 (254)	10 (254)
Stroke length(mm)	127	127	127
Air powered range(bar)	1-7	1-7	1-7
Maximum pressure (psi; bar)	4568 (315)	5685 (392)	6903 (476)

Marketed by:

ABRADANT INTERNATIONAL | Dubai Investment Park 2 | Dubai | UAE
Tel : +971-488-76357 | Email : info@abr-intl.com | www.abr-intl.com